
# SHURE MICROPHONES

PICKUPS • CUTTERS • STANDS • ACCESSORIES



# SHURE CARDIOID MICROPHONES

Solve Sound Problems in Public Address, Broadcasting and Recording




Shure Cardioids are working wonders for Sound Engineers in every type of installation. A simple "ear" test quickly tells how effectively they solve troublesome sound problems—how greatly they improve the pick-up and reproduction of voice and music. Shure Cardioids bring you all the advantages of true uni-directional performance at low cost. They provide smooth wide-range reproduction from 40 to 10,000 cycles over a wide angle at the front (both horizontally and vertically) which diminishes sharply to a pronounced dead zone at the rear (down 12-15 db at rear). You get the sound you want, as you want it.

IN PUBLIC ADDRESS. What a difference—when you plug a Shure Cardioid into the amplifier. You can get more volume without feedback—cut down the pick-up of audience and background noise—reduce reflected sound and reverberation effects 66%—and permit performers to move about more freely. Where necessary, you can place the microphone and loud speakers close together for better audience coverage. All this makes it easier to set up your sound system in any location without worrying about room acoustics or outdoor problems. You also add modern beauty to your entire sound system. That is why Sound Engineers in all parts of the world are replacing ordinary microphones with Shure Cardioids on existing sound installations and using Cardioids on news systems, too—in theatres, night clubs, auditoriums, schools, churches and similarly difficult acoustic locations!

IN BROADCASTING AND RECORDING. The Shure Cardioid, of course, is ideal for studio work—and essential when you take a microphone out of the studio on remote pick-ups. The Cardioid cuts down reverberation effects—reduces random noise pick-up—gives prominence and definition to the direct sound at the front of the microphone. In small studios it permits you to place the microphone with its back close to the studio wall without worrying about troublesome reflections. This facilitates microphone placement—simplifies microphone technique—improves sound quality. When you consider its excellent performance and comparatively low cost, you can readily understand why more and more prominent broadcast stations and recording studios are adopting the Cardioid as standard equipment.


THE SHURE "UNIPHASE" PRINCIPLE. Only the Shure Cardioids give you all this at such surprisingly low cost! The outstanding development of the *Uniphase* principle by Shure Engineers (Shure Patents Allowed) made possible for the first time true cardioid uni-directional performance in a *single* microphone element instead of two. This eliminates the necessity of matching two dissimilar units in one microphone. This means *uniformity* and *economy* in production—and low cost to you. Provides extra ruggedness, too.

DYNAMIC AND CRYSTAL. Shure Cardioid Microphones are available in *Uniplex Crystal* and *Unidyne Dynamic* models illustrated and described on the opposite page.



#### **Ordinary Microphone**

Shows how feedback occurs with conventional Microphones. Sound from loud-speakers reaching the Microphone directly and by reflection from walls, ceiling, and floor, flows around the case and into the front of the Microphone, and is again reproduced. Ordinary microphones also pick up background and audience noise.



#### Shure Cardioid

Shows how Shure "Cardioid" Microphone picks up sound over a wide angle at the front but is dead at the rear. Sounds flowing around the case from the rear are cancelled by the sounds entering the "Uniphase" acoustic network. Reduces feedback, cuts down troublesome reflections and background noise pick-up—gives true uni-directional performance.



It's "Goodbye Feedback" when you install this famous Shure "Uniplex"—the lowest priced true cardioid microphone. High quality reproduction from 30 to 10,000 cycles over

a wide angle at the front, yet practically unaffected by sound approaching from the rear. (Rear response down approximately 15 db.) Uses exclusive Shure "Uniphase" principle. Output level: 63 db below 1 volt per bar. Specially moisture-proofed Grafoil Bimorph Crystal. Swivel-head. Distinctively

modern, streamlined case design, finished in Satin Chrome. Built-in cable connector. Locking plug attached to cable. Standard 5%"-27 thread. Diameter 3½", depth 3¾". Shipping weight 1½ lbs. (Shure Pat. 2,198,424).

Model 730A. "UNIPLEX" Cardioid Crystal Microphone.

Model 730A. "UNIPLEX" Cardioid Crystal Microphone. Complete with 25 ft. super shielded rubber-covered cable. Code: Rupel.
List Price \$3250

List Price.

#### "UNIDYNE" CARDIOID DYNAMIC

Today's most popular true uni-directional microphone. Specially suspended double wind-screened moving-coil system. Employs exclusive Shure "Uniphase" principle. Smooth response from 40 to 10,000 cycles. Wide angle pick-up at front, dead at rear (down 12-15 db). Rugged, shock-proof construction. Practically unaffected by heat and humidity. Ideal for severe outdoor and indoor service. Head tilts through 90 degree angle. Built-in cable connector. Satin Chrome finish. Permissible cable length practically unlimited on low impedance models. Standard \( \frac{5}{2}\frac{\pi}{2}\) 27 thread. Case dimensions: \( 4\frac{1}{4}\) migh; \( 3\frac{1}{2}\) wide, \( 3\frac{1}{2}\) deep. Shipping weight \( 4\frac{1}{4}\) lbs.

Model 55A. Low impedance. For 35-50 ohm circuits. 25 ft. two-conductor shielded rubber-covered cable. Output level into 50 ohms: 62.8 db below 6 milliwatts for 10 bar signal.

Model 55B. Low impedance. For 200-250 ohm circuits. Includes internal transformer. 25 ft. two-conductor shielded rubber-covered cable. Output level into 250 ohms: 63.8 db below 6 milliwatts for 10 bar signal. Code: Rudat.

**Model 55C.** High impedance. May be used with any crystal microphone amplifier or other amplifier with input impedance of 100,000 ohms or more. Includes internal transformer. 25 foot single conductor shielded cable. Output level: 55.5 db below 1 volt per bar. Code: **Rudas**.

List Price \$45.

#### "555" BROADCAST CARDIOID DYNAMIC

Broadcast Stations and Recording Studios are rapidly replacing present equipment with this new Shure 555 Broadcast Unidyne. Exclusive Shure "Uniphase" principle provides true cardioid uni-directional performance at surprisingly low cost Smooth response from 40 to 10,000 cycles at front; dead at rear (down 12-15 db). Extremely rugged construction. Specially-suspended double wind-screened moving coil system. Built-in transverse vibration isolation unit. Swivel head. Satin Chrome finish. Standard 5%"-27 thread. Easily adapted to fit stands with other threads. Equipped with 18" stub of rubber-covered two-conductor shielded cable, trimmed on free end for attachment of connector plug. Stub may easily be replaced by longer length of cable if desired. Case dimensions: 4½" high, 3¾" wide, 3½" deep. Shipping weight 4½ lbs. (Call Letter Plate not included).


Model 555B. Broadcast "Unidyne" Dynamic, for 200-250 ohm circuits. Includes internal transformer. Output level into 250 ohms: 63.8 db below 6 milliwatts for 10 bar signal. Code: Rudif.

List Price......\$60

Model 555C. Broadcast "Unidyne" Dynamic. High impedance. Includes internal transformer. Output level: 55.5 db below 1 volt per bar. Code: Rudiv.

List Price.....\$60

Shure Patents Allowed on All Above Microphones



### **Shure Wide-Range Best in**

These Shure-Engineered Dynamic Microphones provide smoother, wide-range response in comparison to other general-purpose dynamics. No annoying peaks or distortions. Moving-conductor type. Functionally designed and beautifully styled. Extra rugged—not affected by heat or humidity—ideal for indoor and outdoor use in any climate. Low impedance models permit practically unlimited cable length. High impedance model may be used with crystal microphone amplifier or any amplifier with input impedance of 100,000 ohms or more. Built-in high quality matching transformer. Standard  $\frac{5}{8}$ "-27 thread for stand mounting.

## Shure DYNAMIC

#### "508" STRATOLINER DYNAMIC

#### Newest Design • Improved Performance • Added Features!

A new dynamic leader in beauty and performance for general-purpose public address, remote broadcasting, recording, call systems, and other applications indoors and outdoors. Excellent wide range frequency response. Output level: Low Impedence Models, 68 db below 6 milliwatts for 10 bar signal; High Impedance Model, 60 db below 1 volt per bar. Strikingly modern, die cast case in Iridescent Gray highlighted in Satin Chrome. Semi-directional or non-directional operation. Swivel head easily aimed at source of sound for best response. Built-in cable connector. Locking microphone plug attached to cable. Diam.  $2\frac{1}{2}$ , length  $4\frac{1}{16}$ . Shpg. wt.  $2\frac{3}{4}$  lbs.

Model 508C. High Impedance Dynamic. Complete with 25 ft. single-conductor, shielded rubber-covered cable. Code: Rudob.

List Price \$2750

### "500" DYNAMIC Streamlined for Low-Cost Public Address!

Excellent dynamic performance at low cost. Assures faithful reproduction of voice and music. Sturdy, attractive die cast case finished in Iridescent Gray with highly polished plating on front grille. Output level: Low Impedance Models, 71.8 db below 6 milliwatts for 10 bar signal; High Impedance Models, 63 db below 1 volt per bar. Diameter 23%". Spring cable protector. Shpg. wt. 2½ lbs.

Model 500C-7Ft. High Impedance Dynamic. 7 ft. single-conductor shielded rubber-covered cable. Code: Rudix.

List Price.

\$1750

Model 500C. High Impedance Dynamic. 25 ft. single-conductor shielded rubber-covered cable. Code: Rudig.

Model 500A. Low Impedance Dynamic. For 35-50 ohm lines. 25 ft. two-conductor shielded rubber-covered cable. Code: Rudir.

Model 500B. Low Impedance Dynamic. For 200-250 ohm lines. 25 ft. two-conductor shielded rubber-covered cable. Code: Rudik.

List Price.....\$19.00

Model. A86A. High Quality Cable-Type Transformer to match 35-50 ohm and 200-250 ohm microphones to high impedance amplifier input. Code: Rudeb.

List Price.....\$10.00

**General-Purpose Microphones** 

The exceptional performance of these Shure Crystal Microphones has made them favorites the world over for high quality sound installations. Smooth high quality wide-range response. Insures excellent reproduction of voice and music. High output level. Specially moisture-sealed Grafoil Bimorph Crystal. Complete barometric compensation. Sturdy die cast cases in rich Satin Chrome finish. Built-in cable connector. Locking microphone plug attached to cable. Standard  $\frac{5}{8}$ "-27 thread for stand mounting.

### Shure CRYSTAL

#### **705A "ROCKET" CRYSTAL**

"Ultra" in Beauty and Performance

Beautifully modern in every way! Smooth "Ultra" wide-range response from 30 to 10,000 cycles. Output level: 58 db below 1 volt per bar. Semi-directional or non-directional operation. Swivel head easily aimed at source of sound for best response. Internal screen protected cartridge, mechanically isolated. Diameter  $2\frac{3}{8}$ ". Length  $3\frac{1}{16}$ ". Shpg. wt.  $2\frac{1}{2}$  lbs.

#### **70H "SUPER-LEVEL" CRYSTAL**

#### **Highest Output Available Today!**

For years—the "standby" among sound men for dependable high quality performance. Excellent wide-range response. Has the highest output level available today in crystal microphones: 47.5 db below 1 volt per bar (27.5 db below 1 volt for 10 bar signal). Requires less amplifier gain—provides a useful margin of extra sensitivity when needed. Diameter  $3\frac{3}{16}$ ". Depth  $1\frac{3}{8}$ ". Shpg. wt. 2 lbs.

#### **700D "ULTRA" CRYSTAL**

#### Highest General-Purpose Performance

Famous for its fidelity of reproduction and dependable service. Smooth "Ultra" wide-range response from 30 to 10,000 cycles. Output level: 58 db below 1 volt per bar. Small, compact, swivel head for semi-directional or non-directional operation—easily aimed at source of sound for best response. Internal screen protected cartridge, mechanically isolated. Diameter 23/8". Shpg. wt. 21/4 lbs.

SHURE DIRECTIONAL BAFFLES. Discriminate against pick-up of high-frequency sounds from sides and rear of microphone; reduce feedback; cut down room-noise pick-up. Snap into place; easily detached. Satin Chrome finish. Outside Diameter 4". Shpg. wt. ½ lb.





SHURE leadership in microphone engineering, design and construction assures you of finer quality and performance than anything else in this low price field.

#### **708A "STRATOLINER" CRYSTAL MICROPHONE**

Modern as Tomorrow—Low in Cost!

Improves appearance of sound set-ups-gives quality reproduction of voice and music for low-cost public address, call systems, home recording and other general-purpose apcan systems, nome recording and other general-purpose applications. Excellent, smooth frequency response. High output level: 49.7 db below 1 volt per bar at end of 7 ft. cable. Moisture-sealed Bimorph Crystal, mechanically isolated. Beautifully designed die cast case in Iridescent Gray highlighted in Satin Chrome. Semi-directional or nondirectional operation. Swivel head easily aimed at source

of sound. Built-in cable connector, Standard  $\frac{5}{6}$ "-27 thread for stand mounting. Diameter  $2\frac{1}{2}$ ". Length  $\frac{4}{16}$ ". Complete with 7 ft. single-conductor rubber-covered shielded cable, with microphone locking-plug attached. Shpg. wt. 2½ lbs.

Model. 708A. "Stratoliner" Crystal Microphone \$1750 Code: Rudum. List Price.... Model 708A-25 Ft. Same, with 25 ft. cable. Code: Rudup. List Price.....

#### 707A CRYSTAL MICROPHONE

Nothing like it at this low cost! Smooth frequency response for voice and music. High output level: 49.7 db below one volt per bar at end of 7 ft. cable. Modern die cast case finished in Iridescent Gray with highly polished plating on front grille. Moisture-sealed Bimorph Crystal, mechanically isolated. Standard 5/8"-27 thread. 7 ft. single-conduc-

tor, shielded rubber-covered cable with spring protector. Diam. 23%. Shpg. wt. 134 lb.

Model 707A. Crystal Microphone. Code: Rudof.

\$995

Model 707A-25 Ft. Same with 25 ft. cable. Shpg. wt. 21/4

lbs. Code: Rudug. List Price......\$11.50

#### 717A CRYSTAL HAND MICROPHONE

New Lightweight "Tenite" Design

A new lightweight hand microphone developed by Shure Engineers. Beautiful **Tenite** resilient plastic case and handle—rugged, handy to use. Smooth response, suitable for both voice and music. High output level: 49.7 db below one volt per bar at end of 7 ft. cable. Moisture-sealed Bimorph Crystal, mechanically isolated. Diam. 21/2", height overall 6", depth 1½". Complete with 7 ft. single-conductor shielded rubber-covered cable. Shpg. wt. 34 lb.

Model 717A. Crystal Hand Microphone. Code: Ruduk. List Price....

### **Shure Communications Microphones**

Best for Amateur, Police and Commercial 'Phone

Shure Crystal "Speech" Microphones are "heard 'round the world" in important Communications work. The Shure-Engineered "highefficiency" speech characteristic gives clear, crisp signals, cuts through noise and static. Built-in R.F. filter protects against burnouts. Moisture-sealed Grafoil Bimorph Crystal. Beautifully styled sturdy die cast cases. Built-in cable connector. Locking microphone plug attached to cable. Standard \( \frac{5}{8}\)"-27 thread.

#### "STRATOLINER" CRYSTAL

The beautiful new "Stratoliner" with special Shure speech characteristic for commercial and amateur 'phone. High output level, 29.7 db below 1 volt for 10 bar speech signal. Swivel head easily aimed at source of sound. Iridescent Gray finish highlighted in Satin Chrome. Diam.  $2\frac{1}{2}$ ", length  $4\frac{7}{16}$ ". Shpg. wt.  $2\frac{1}{2}$  lbs.

#### "UNIPLEX" CRYSTAL CARDIOID

#### Makes Break-in Phone Easy!

Famous "Uniplex" model with special Shure speech characteristic! Dead at rear. (Rear response down 12-15 db). Gives studio performance. Cuts down room-noise pick-up, eliminates echoes, assures clearer, more intelligible speech. Cleans up voice transmission. Makes break-in 'phone easy. Ideal for police, commerciand high quality amateur communications. Output level: 33 db below 1 volt for 10 bar speech signal. Swivel head easily aimed at source of sound. Rich Satin Chrome finish. Diameter 31%". Depth 33%". Shpg. wt.  $1\frac{1}{2}$  lb.

#### **70STH "SUPER-LEVEL" CRYSTAL**

Here's the world-famous Shure "Super-Level" Crystal Communications Microphone. Has Shure high-efficiency speech characteristic with the highest output available in a crystal microphone: 26 db below 1 volt for 10 bar speech signal. Diameter  $3\frac{3}{16}$ ". Depth  $1\frac{3}{6}$ ". Satin Chrome finish. Shpg. wt. 2 lbs.

Model 70STH. Crystal Microphone without desk mount. Complete with 7 ft. shielded rubber-covered cable. Code: Rupic.
List Price. \$2250

Model 7057. Same, complete with Model S36A Iridescent Gray Desk Mount. Shpg. wt. 3½ lbs. Code: Rupib.

#### "MILITARY-TYPE" HAND MICROPHONE

Fits naturally, comfortably in palm of hand. Light, compact. Takes minimum space in portable equipment. Sturdy die cast case in attractive Iridescent Gray with Satin finish grille. Excellent frequency response. Output level: 32.5 db below 1 volt for 10 bar speech signal. Specially designed "ON-OFF" switch—locks in the "ON" position when pushed up—operates "ON-OFF" in the down position. Switches to control external circuits can be furnished on special order. Complete with removable suspension hook, 7 ft. shielded rubber-covered cable and spring cable protector. 3¾" high, 2¾" wide, 1¾" thick. Shpg. wt. 1 lb.

Model 750B. "Military-Type" Crystal Hand Microphone complete with switch. Code: Rusel.

List Price. \$2250

(Carbon Type "Military" Hand Microphones are available in quantity only, on special order.)









# ...And SHURE Meets the Need Here, Too!

#### **76B Lapel Crystal Microphone**

Small, light Crystal Lapel Microphone with high output level. Gives high quality reproduction of speaker's voice. Inconspicuous. Only 1½ oz. Iridescent Gray finish. Handy lapel clip. Complete with 25 ft. shielded rubber-covered single-conductor cable. Shpg. wt. 1 lb.

Model 76B. Lapel Microphone. Code Rulop. List Price.....

#### 61B Crystal Vibration Pickup

The Shure Vibration Pickup-Used for locating and measuring vibration, checking surface smoothness, and for the solution of a wide variety of scientific and industrial problems. No plungers or other external moving parts. Triple-moisture-sealed Grafoil Bimorph Crystal. May be fastened to object or used with extension rod for point-to-point tests. Black wrinkle finish. Complete with 8" extension rod, ball tip, point tip, mounting bracket, and 7 ft. shielded rubber-covered cable. Case 2½" by 2½" by 1¾". Shpg. wt. 1½ lbs. Model 61B. Vibration Pickup. General-purpose type. Linear acceleration characteristic to 1300 cycles. Code: Ruteb.

#### **66D Crystal Stethophone**

List Price.....

A non-acoustic piezoelectric Stethophone for pickup of heart and chest sounds. Special "anti-noise" construction practically eliminates air-borne noise. Output: 5 to 10 millivolts. Only 15/6" in diameter; net weight less cable, 3 oz. Satin-Chrome finish. Complete with protective cap and 7 ft. shielded rubber-covered cable. Shpg. wt. ¾ lb.

Model 66D. Stethophone. Code: Rutef. List Price.....

#### Microphone Repair Service

All microphones require occasional repairs. Carbon microphones need reconditioning at least once a year to maintain sensitivity and quality. Shure "Microphone Headquarters" maintains a special department for repairing and reconditioning many types and makes of microphones. Write for quotations.

#### **Laboratory Non-Directional Microphone**

Shure Non-Directional Crystal Microphone designed for scientific and industrial sound measurement work-and for high quality sound reproduction in broadcasting, professional recording and other applications. High fidelity flat response from 30 to 10,000 cycles in the horizontal plane. Output level: 58.3 db below 1 volt per bar open circuit (61.5 db below 1 volt per bar at end of 25 ft. cable). Diam. 21/4". Built-in cable connector. Satin Chrome finish. 25 ft. shielded rubber-covered single-conductor cable. Show with 2 lbs. 

furnished for \$10.00 net.

#### 3B Two-Button Carbon Microphone

Full-size two-button microphone with quality performance for ama-

#### **5B Two-Button Carbon Microphone**

High quality, full-size two-button microphone. Regular full-size pre-

#### 10B Two-Button Hand Microphone

Convertible Hand Microphone—convenient for general-purpose public address use! Easily changed from hand to 3B type for stand mounting by removing handle. Iridescent Gray handle. Overall 



# SHURE STANDS



#### "Stabilized" Friction-Lock Floor Stands

Beautiful, sturdy Shure Floor Stands help improve any sound set-up! Height adjustments made easily, quietly, with super-positive lifetime guaranteed Friction Lock. Only a fraction of a turn to lock, yet supports a 50 lb. load. Scientifically designed 3-point "Stabilized" base cushioning with pure gum rubber gives 10-18 db reduction of shock and vibration. Base locks outer tubing securely in place . . . will not let it turn or twist. Molded soft rubber cable guide holds cable neatly and securely in place. Standard  $\frac{5}{8}$ "-27 thread.

Model \$50B. Floor Stand. Satin Chrome finish. Modern round base with fluted rim (diam. 9½"; wt. 8 lbs.). Height adjustment 443%" to 70½". Shpg. wt. 11½ lbs. Code: Rusaf. List Price.....

Model \$51B. Floor Stand. Satin Chrome finish. Beautiful Tenite plastic ornament at base. Large modern round base with fluted rim (Diam.  $10\frac{1}{2}$ "; wt. 10 lbs.). Height adjustment  $44\frac{5}{8}$ " to  $70\frac{3}{4}$ ". Shpg. wt.  $13\frac{1}{2}$  lbs. Code: **Rusif.** 

Model 555A. "Studio-Type" Floor Stand. Heavy 3-leg base (Wt. 10½ lbs.). Height adjustment, 48" to 70". Leg spread 15½". Iridescent Gray finish. Shpg. wt. 14 lbs. Code: Rusat. List Price...

#### **3-Section Utility Stand**

Model **\$54C.** 3-section Floor Stand. Especially suitable for portable use. Shure Friction-Lock makes height adjustments easy. Modern round base with fluted rim. (diam. 9½"; wt. 8 lbs.). Iridescent Gray finish. Ht. range 30" to 64". Shpg. wt. 111/2 lbs. Code: Rusap. List Price.....

#### **Heavyweight Broadcast Floor Stand**

S510A Floor Stand functionally designed for exacting Broadcast and Recording use. Low "stabilized" extra heavy 3-leg base hugs floor and provides firm footing. Pure gum rubber base isolation. Quick, positive, foolproof, Friction-Lock permits instant, smooth, stable height adjustment from 45" to 79". Extra-heavy non-vibrating large-diameter tubings, finished in Satin Chrome. "Free-wheeling" mounting screw with \( \frac{5}{8}\) "-27 male thread for easy attachment or removal of microphone. Inner tubing has \( \frac{1}{2}\)" pipe thread outside and \( \frac{5}{8}\)"-24 machine thread inside for mounting other types of microphones. Base leg spread \( 16\) \( \frac{1}{2}\)"—shaped to give maximum floor space for artists—finished in Baked Enamel. Net wt. of tubing assembly \( 6\) \( \frac{1}{2}\) lbs. Net wt. of base \( 22\) \( \frac{1}{2}\) lbs. Shpg. wt. 32 lbs. 61/2 lbs. Net wt. of base 221/2 lbs. Shpg. wt. 32 lbs. Model 5510A. Broadcast Floor Stand. Code: Rusop.


List Price

#### **Modern, Practical Desk Stands**

Model \$36A. Beautiful, streamlined Desk Mount, with stable support at correct height. Fits Shure connector-type microphones, concealing plug in base. Adapter plate and tubing provided for other type microphones. Ornamental button at 

Model \$32D. Highly attractive, modern Desk Stand, finished "Friction-Lock" provides easy, positive height adjustment from 7" to 11". Standard \( \frac{5}{8}\)"-27 thread. Base diam. 6". Shpg. wt. 3½ lbs. Code: Rused. List Price.....

Model \$34A. Take-Apart Stand. New handy low cost stand for desk and hand use. One twist of handle locks it securely in base for use as desk or table stand, or releases handle for use in hand. Metal base, wood handle. Brass ferrule at top threaded 5%"-27. Ht. overall 611/6". Base diam. 41/2". Length of handle 57%". Shpg. wt. 1 lb. Code: **Rukab.** List Price





### SHURE MICROPHONE ACCESSORIES

#### For Practical Convenience and Utmost Efficiency

<b>Model A32A.</b> ELASTIC ISOLATION UNIT. For use with Shure "555" Broadcast Microphone when mounted on floor stand. Extremely effective against vibrations transmitted through the stand. Recommended where excessive vibration conditions exist. Modern, unique, offset design. Satin chrome finish. $5\%$ "-27 thread for easy attachment or removal. Has thumb screw operated cable clamp for strain relief. Case Dimensions: $1^{13}\%$ " high, $2''$ wide, $4^{5}\%$ " long. Net weight 1 lb. 10 oz. Shipping weight, 2 lbs. Code: <b>Rudib.</b> List Price
Model A83A. MICROPHONE "ON-OFF" SWITCH. Quiet rotary type. Short-circuits microphone line in "OFF" position. Easy to install and use with Shure connector-type microphones. Internal plug makes the connection—no wiring necessary. Built-in receptacle for Shure standard cable-connector plug. \( \frac{5}{8}'' - 27 \) thread. Satin Chrome finish. Bakelite arrow knob. Size 1\( \frac{3}{4}'' \) high x 1\( \frac{1}{8}'' \) wide x 2'' deep. Furnished without cable. Shpg. wt. \( \frac{3}{4} \) lb. Code: Runim. List Price
Model A80B. MICROPHONE "ON-OFF" SWITCH. Threaded 5/8"-27 to fit non-connector type microphones. Rotary-type. Small Bakelite arrow knob. Satin Chrome finish. Case dimensions, 21/8" high, 11/8" wide, 11/8" deep. Unwired, without microphone cable or plug. Shpg. wt. 71/2 oz. Code: Runib. List Price
Model A84A. MOMENTARY "ON-OFF' SWITCH. Press-to-talk push-botton type. Easily attached to Shure connector-type microphones, as above A83A. 5%"-27 thread. Satin Chrome finish. Bakelite disc. Operates easily with thumb or palm of hand. 1¾" high x 1½" wide x 2" deep. Without cable. Shpg. wt. ¾ lb. Code: Runid. List Price
Model A85A. MOMENTARY RELAY-TYPE SWITCH. Same "hand control" as A84A. Normally-open switch closes circuit comprising one conductor and shield of outgoing cable for operation of relay or other device; remaining conductor and shield of cable carry microphone output. Must be used with two-conductor shielded cable, and only with crystal and high impedance dynamic microphones. Standard Shure cable-connector receptacle. Satin Chrome finish. Bakelite disc. 1¾" high x 1½" wide x 2" deep.

Model R10B. RING. A light 5" ring for small carbon microphones. Satin-Chrome finish. 8 rust-proof springs. Shpg. wt. ¾ lb. Code: Rujes. List Price.......\$2.25

Model A72A. CALL-LETTER PLATE. Attractive cast-aluminum call-letter plate for Shure "555" Broadcast Microphones. Fits on the case of the microphones easily and snugly. Makes call letters visible from all four sides, with practically no effect on directional characteristics of microphone. (Lettering can easily be applied by user). Satin and black finish. Dimensions: 75½" high, 6½" wide, 1½" deep. Net weight 6½ oz. Shipping weight 12 oz. Code: Rudic. List Price. \$10.00

MICROPHONE CABLE—available in standard trimmed 7 ft. and 25 ft. lengths. Other lengths in bulk untrimmed:

**Model C10C.** CABLE. For crystal and high-impedance dynamic microphones. Low capacity and high insulation resistance. Single-conductor type with close shield. Overall rubber jacket. Code: **Rusob.** List Price, per ft......**10c** 

For Shure microphone locking-plug attached to cable, add \$1.50 list. Cordsets complete with Shure microphone plug and amplifier input plug, completely wired, are available to fit most amplifiers. State amplifier make and model number.




Shure 94A "Economy" Crystal Pickup

Designed for compact record players! Mounts in minimum space. Plays 10" and 12" records. Has Shure "needle-tilt" Balanced-Tracking. Triple-moisture-sealed Grafoil Bimorph Crystal. Full range frequency response. Output, 2½ volts. Low needle pressure. Floating rubber-cushioned pivot bearing assembly for single-hole mounting. Attractions pivot bearing assembly for single-hole mounting. Attractive cast arm. Smooth brown finish. Length 7½6". Comtive cast arm. Smooth brown finish. Length 715/6". Complete with 20" shielded cord, arm rest and motorboard drilling template. Shpg. wt. 3/4 lb.

Model 94A. Crystal Pickup. Code: Ruzec. List Price.....

\$495



stylus. Code: Ruzad. List Price.....

#### Transcription-Type Crystal Pickups

Meet the latest requirements for high quality reproduction of lateral records in broadcasting, recording and public address work. Smooth high frequency response. Full bass response adjustable with simple networks in the input circuit. Output approximately 2½ volts. Grafoil Bimorph Crystal, triple-moisture-sealed. Easy needle-changing. Head locks in place when tilted back. Arm locks in place when swung away from turntable. Needle-pressure 23/4 ounces. Statuary Bronze finish overall. Complete with  $3\frac{1}{2}$  ft. shielded cord, mounting screws and

motorboard drilling template.

Model 9108. For 10" and 12" records. Straight-arm design, with Shure "needle-tilt' Balanced Tracking. Overall length 1034". Shpg. wt. 2 lbs. Code: Ruzil.

List Price.

\$1550

Model 914A. For 16", 12" and 10" records. Bent arm tracking correction. Overall length, 12 \%". Shpg. wt. 2 lbs. \$16<sup>50</sup> Code: Ruzig. List Price.....


#### Crystal Pickup Replacement Cartridges

**Model W20C.** Metal type cartridge that fits Shure 99, 94 and 910 pickups. Has built-in "Needle-Tilt" Balanced-Tracking. Case:  $1\frac{7}{8}$ " long,  $\frac{7}{16}$ " wide, 

Model W27C. Bakelite type cartridge for universal replacement. Three-in-one 

### SHURE LEADS THE WAY TO BETTER SOUND





SHURE GUARANTEE—Every Stare Product is guaranteed to be free from electrical and mechanical defects for one year from date of shipment from the factory, provided all instructions are complied with fully.













Shure Engineering holds an eminent position in the sound field. It has pioneered many important developments which have contributed greatly to better sound. Thru constant research and development, Shure Microphones, Acoustic Devices, and other products are engineered to give the best kind of performance for their specific application and are functionally designed by prize-winning Industrial Designers to provide distinctive beauty and case of operation. That's why they have long been specified by sound engineers and amateurs, by designers and manufacturers of sound equipment, by broadcast and recording engineers. And now again—in Home Recording, Shure leads the field. Shure Microphones have been adopted as standard equipment by more manufacturers of Home Recorders than any others.

Complete technical data available on any item. \* All Prices Subject to Change Without Notice. \* Shure Patents Pending. Crystals devices licensed under patents of Brush Development Co.

Copyright roso Shure Brothers, Chicago, Printed in U.S.A. 153-1030-50C.



SHURE BROTHERS - 225 W. HURON ST. - CHICAGO, U. S. A. - CABLE: SHUREMICRO DESIGNERS AND MANUFACTURERS OF MICROPHONES AND ACOUSTIC DEVICES