

Rowe
AMI

MODEL
M

200 SELECTION, HIGH FIDELITY

PHONOGRAPH

. . . with exclusive S T E R E O R O U N D Sound System
convertible to 160 or 100 selections



MODEL JBM-200 - SPECIFICATIONS

Dimensions:

Depth 27-1/4 inches
Width 34 inches
Height 54-1/16 inches

Net Weight 332 pounds
Shipping Weight 372 pounds

POWER REQUIREMENTS:

115 V.A.C., 60 C.P.S., 330 Watts

LIGHTING

Animation Box . . . #10C75 DC-12V. Incandescent Lamps (2) (200-09742)

Front Door Panel . . . 28" 25 Watt T-12 Fluorescent Lamp (1) (705-00601)

Credit Window . . . #47 Incandescent Lamp (1) (220-02232)

Personalization (YOUR HOST) . . .

33" 25 Watt T-12 Fluorescent Lamp (1) (706-00601)

Mechanism Shelf . . . 24" 20 Watt T-12 Fluorescent Lamp (1) (704-00601)

FUSES:

Junction Box . . . 8 Amp. GLH Fusetron (1) (702-00720)
2.8 Amp. MDL Slo-Blo Fusetron (2) (716-00721)

Power Amplifier . . . 2.8 Amp. MDL Slo-Blo Fusetron (2) (716-00721)

Credit Unit . . . 8/10 Amp. MDL Slo-Blo Fusetron (1) (702-00721)

AMPLIFIERS TUBE TYPES:

Control Amplifier . . . 6AW8A (2) (200-09746)
12AT7/ECC81 (1) (200-11456)
7025/ECC83 (2) (200-08333)

Power Amplifier . . . 12AX7 (2) (200-02633)
5U4GB (1) (200-00195)
7868 (4) (200-09614)

The following is a quick reference list of the self-contained major components included in the Model M phonograph. (Breakdown for all of these are in the PARTS SECTION of this manual):

Record Changer Mechanism . . . (606-03000)	Phono. Speakers
Automatic Selector . . . (601-03270) —	12" Low Frequency . . . (400-02539)
Amplifiers:	4" x 6" High Frequency . . . (300-03745)
Control . . . (601-02680)	6" x 9" Mid Range (2) . . . (400-05290)
Power . . . (601-02620)	Credit System:
	Slug Rejector . . . (402-01281)
	Junction Box . . . (401-05218)
	Credit Unit . . . (605-01473)

ACCESSORY EQUIPMENT . . . (Optional)

- MODEL CFA STEPPER UNIT (605-02648) . . . for use with AMI, Wurlitzer 200, Seeburg 200 and Rock-Ola 200 Wall boxes.
- MODEL CFD STEPPER UNIT (606-02648) . . . for use with Seeburg 100 Wall boxes.
Both of these units are the successors to the CEA and CED Respectively, and feature improved circuitry and lower voltage operation.
- AUXILIARY POWER SUPPLY (PL-10A) . . . This unit allows wall box, low voltage operation separate from that required for the phonograph but retains the AC CONTROL feature which is desirable in some wall box operations.
The PL-10A is for locations having one or more wall boxes operating one ROWE AMI phonograph.
- FRONT, DECORATIVE PANEL (600-03274) (Wood Grain Finish) . . . This panel provides a toned-down, more sophisticated effect for location environment warranting this effect.
- CONVERSION KIT (200-65018) (160 and 100 selection operation) . . . This kit contains the decorative, title display parts necessary for conversion from 200 to 160 or 100 selections.
- COUNTER WEIGHTS KIT (201-65016) (160 and 100 selection operation) . . . These parts are for counter balancing, and blocking off, the record magazine slots which are not used when either 160 or 100 selection operation is desired.
- SWITCH KIT (201-65017) (160 and 100 Selection Operation) . . . This provides automatic cancel when a record is not placed on the turntable.
- EX-600 CYLINDRICAL, REMOTE SPEAKER (602-02004).
- RC-800 MULTIPLE SPEAKER REMOTE VOLUME CONTROL (300-03382).
- RC-600 INDIVIDUAL SPEAKER REMOTE VOLUME CONTROL (306-03333) ("L" pad).
- RC-700 INDIVIDUAL SPEAKER REMOTE VOLUME CONTROL (300-03387) (Flush mount "L" pad).
All of the above accessories and kits include mounting parts and installation instructions.