



- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL RESISTORS ARE ± 5%, 1/4W.
 2. PREFIX ALL REFERENCE DESIG. WITH ASSEMBLY REFERENCE DESIG. "A"
 3. * INDICATES 'AID' TEST POINT.

DIE SIZE — C.C. — FT. PER M — LBS. PER M —

ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF BALLY MFG. CO. CHICAGO, ILL. THIS INFORMATION IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS IN PART OR IN WHOLE WITHOUT THE EXPRESS CONSENT OF THE OWNER. THE PRINT IS LOADED AND MUST NOT BE USED IN ANY MANNER DETERMINED TO BE IN THE INTEREST OF THE OWNER, AND MUST BE RETURNED ON DEMAND.

REMOVE ALL BURRS		DR. BY	DATE	Bally MANUFACTURING CORP #1120-E	
TOLERANCES ON DIMENSIONS UNLESS OTHERWISE SPECIFIED		EX. BY	DATE	2640 BELMONT AVENUE CHICAGO, ILLINOIS	
FRACTIONS:		APPROV. BY	DATE	ALL NOVELTIES	
DECIMALS:		DATE	CONTROL	ISS. NO.	SCALE
ANGLES:		DATE	ISS. NO.	ISS. NO.	SCALE
DO NOT SCALE DRAWING		DATE	ISS. NO.	ISS. NO.	SCALE
HARDENING:		DATE	ISS. NO.	ISS. NO.	SCALE
MATERIAL:		DATE	ISS. NO.	ISS. NO.	SCALE

1	A	WAS	500V	4/8/78	TD
NO.	LET.	CHANGE	DATE	BY	CK.

PART NO. W-1184-1c