

SCHEMATIC OF THE HEATHKIT® TRANSISTORIZED REGULATED POWER SUPPLY MODEL IP-20

ALL RESISTANCES IN OHMS K = 1000.
ALL RESISTORS 1/2 WATT UNLESS OTHERWISE SPECIFIED

NOTES:

1. ALL VOLTAGES TAKEN AT 117 VOLTS, 60 CPS INPUT.
2. ALL VOLTAGES READ WITH A VTVM.
3. CONTROLS SET AS FOLLOWS FOR VOLTAGE MEASUREMENTS:


VOLTAGE RANGE	5
CURRENT RANGE	1.5 A
FINE VOLTAGE	MAX clockwise
CURRENT LIMIT	MAX clockwise
TOGGLE SWITCH	Reset-standby
METER SWITCH	Voltage

4. ALL VOLTAGES MEASURED FROM NEGATIVE (-) OUTPUT TERMINAL UNLESS OTHERWISE INDICATED. ○ INDICATES VOLTAGE READING.

5. ALL VOLTAGES ARE DC UNLESS OTHERWISE INDICATED.
6. VOLTAGE READINGS CAN VARY ±10%.
7. OUTPUT UNLOADED.
8. ROTARY SWITCHES SHOWN IN MAXIMUM COUNTERCLOCKWISE POSITION.

POSITION OF VR	E1 VOLTS AC	E2 VOLTS DC	E3 VOLTS DC
5	10	14	6
10	15	21	10
15	20	28	15
20	25	35	20
25	29	41	25
30	33	47	30
35	38	54	35
40	43	60	40
45	47	68	45
50	53	74	50

Set controls as in note 3 except for Voltage Range (VR) switch.



**SCHEMATIC OF THE
HEATHKIT®
TRANSISTORIZED REGULATED
POWER SUPPLY
MODEL IP-20**

ALL RESISTANCES IN OHMS $\times 1000$.

ALL RESISTORS 1/2 WATT UNLESS OTHERWISE SPECIFIED.